

FIREPLACE KIT SYSTEM FROM BRUNNER




BSK 01 mit Eck-Kamin 57/52/52

State: 18.11.2014




BRUNNER[®]
made in germany.

Dimension sheet | **BSK 01 mit Eck-Kamin 57/52/52**



... side opening

Dimension sheet | **BSK 01 mit Eck-Kamin 57/52/52**



We suggest for CAD planing Palette CAD. Permanent updated drawings: www.brunner.de
 Frames / front versions are marked colored.

Planning and installation

BSK 01 mit Eck-Kamin 57/52/52

Tested according to

EN 13229

Data for functional demonstration

Rated heat power	kW	10
Firewood consumption	kg/h	3
Flue gas mass flow	g/s	12
Flue gas temperature	°C	210
Necessary supply pressure ¹⁾	Pa	13
Combustion air consumption	m ³ /h	30
Combustion air connection Ø	mm	125

Height extension rings

Ground area (width x depth)	mm	800 x 800
Overall height	mm	1947
Height extension ring	mm	304

Distances

Dist. to adjacent wall in direct contact (with radiation panels inside) ²⁾	cm	0
Dist. to adjacent wall for free-standing design (without radiation panels inside) ²⁾	cm	5
Distance to the ceiling	cm	50

Heat insulation

In ceiling region connection with/without air grate	cm	16 / 12
---	----	---------

Hot air cross section

Supply air ³⁾	cm ²	935
Warm air ⁴⁾	cm ²	900

Weight

Total weight	kg	622 / 550
--------------	----	-----------

meets requirement limit values for:

Germany / Austria / Switzerland / Norway

1.BImSchV (Stufe 2) / 15a BVG / LRV / NS 3059

1) Throttle flap recommended

2) Distance is valid for adjacent walls. For protected walls, a brick lining is required

3) Existing supply air opening in ceiling plate

4) Air supply opening in bottom area must be provided on site

Ulrich Brunner GmbH
Zellhuber Ring 17 -18
D-84307 Eggenfelden
Telefon: +49 / (0)87 21 / 7 71-0
Telefax: +49 / (0)87 21 / 7 71-100
info@brunner.eu | www.brunner.eu

The logo for Brunner, featuring the word "BRUNNER" in a bold, black, sans-serif font. The letters are composed of horizontal lines, giving it a textured appearance. A registered trademark symbol (®) is located at the top right of the logo.